

PH 442 | UL CERTIFIED FUEL DISPENSING AND VAPOR RECOVERY HOSE

FEATURES

Applicable Standard EN 1360 Type 3

- Petrol and diesel fuel dispensing lines of 235 psi pressure
- Inner tube constructed with synthetic rubber resistant to petrol and diesel fuel, available in black color
- Reinforcement with single steel wire braid
- Continuous temperature range of -30°C to +55°C
- 1 x 10² electrical resistance max
- Black cover constructed with synthetic rubber resistant to fuel and weather
- ✓ Available in wrap and smooth* finishes
- ✓ Also available in green and blue

*Smooth cover available in sizes up to 1"

CODE Part Number	Dash Size	DN	ID in mm	OD in mm	WP psi bar	BP psi bar	BR/r in mm	W kg/m
PH442-10	-10	16	5/8 16.0	1.00 25.3	235 16	700 48	3.1 80	0.590
PH442-12	-12	19	3/4 19.0	1.07 27.2	235 16	700 48	3.9 100	0.661
PH442-14	-14	21	7/8 21.0	1.22 31.0	235 16	700 48	5.1 130	0.720
PH442-16	-16	25	1 25.0	1.30 33.0	235 16	700 48	5.9 150	0.657



COMPATIBLE FITTING SERIES	
Insert Series	Ferrule Series
1FD2300X-XXXXXX	2FD10210-XXXXXX

