

# SWISS INNOVATION AT YOUR FINGERTIPS

**Polyhose**<sup>®</sup>

DELIVERING SWISS TECHNOLOGY **EXITFLEX** <sup>+</sup>



## SPEEDY 5

AIRLESS REVERSIBLE TIP • PRODUCTION AND HIGH PRESSURE

**SPRAY WITH CONFIDENCE • SWISS PRECISION FOR U.S. PAINTING CONTRACTORS**

### ERGONOMICALLY DESIGNED

- + Combined **production** and **high-pressure** (7500psi) airless reversible tip in one single design
- + Fits in seconds with unique cone seal design

### COMPATIBILITY GUARANTEED

- + Compatible with all GRACO<sup>®</sup>, TITAN<sup>®</sup>, and TRITECH<sup>®</sup> guards\*
- + RAC<sup>®</sup>5 and XHD RAC<sup>®</sup> compatibility  
*\*not compatible with GRACO<sup>®</sup> RAC X*



- + Fits in Exitflex 5000psi safety guard
- + Ref 88-559 (7/8") or 88-560 (1 1/16")



- + Fits in Exitflex 7500psi safety guard
- + Ref 88-552 (7/8") or 88-557 (1 1/16")

PART NUMBER	DESCRIPTION
88-591-XXX	Reversible tip with seal in blister pack
88-501-XXX	Reversible tip without seal in plastic bag
88-509	Metal seal, only compatible with Speedy 5
88-559	5000psi guard with 7/8" thread
88-552	7500psi guard with 7/8" thread and tip locking mechanism
88-560	5000psi guard with 11/16" thread
88-557	7500psi guard with 11/16" thread and tip locking mechanism

BULK SUPPLY AVAILABLE



SWISS  
MADE

🌐 POLYHOSE.US 📞 732.512.9141 ✉ PHUS.SALES@POLYHOSE.COM

RAC<sup>®</sup> IS A REGISTERED TRADEMARK OF GRACO<sup>®</sup>.  
SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

# SWISS INNOVATION AT YOUR FINGERTIPS

**Polyhose**  
DELIVERING SWISS TECHNOLOGY *EXTIFLEX* 



## SPEEDY 5

AIRLESS REVERSIBLE TIP • PRODUCTION AND HIGH PRESSURE

SPRAY WITH CONFIDENCE • SWISS PRECISION FOR U.S. PAINTING CONTRACTORS

		ORIFICE SIZE INCH																																													
		IN	MM	0.007	0.008	0.009	0.010	0.011	0.012	0.013	0.014	0.015	0.016	0.017	0.018	0.019	0.020	0.021	0.022	0.023	0.024	0.025	0.027	0.029	0.031	0.033	0.035	0.039	0.041	0.043	0.045	0.047	0.049	0.051	0.053	0.055	0.057	0.059	0.061								
FAN WIDTH	2-4	51-102	107	108	109	110	111	112	113	114	115	116	117	118	119	120	121	122																													
	4-6	102-152	207	208	209	210	211	212	213	214	215	216	217	218	219	220	221	222	223	224	225	227	229	231	233	235	239	241																			
	6-8	152-203	307	308	309	310	311	312	313	314	315	316	317	318	319	320	321	322	323	324	325	327	329	331	333	335	339	341	343	345	347	349	351	353	355	357	359										
	8-10	203-254	407	408	409	410	411	412	413	414	415	416	417	418	419	420	421	422	423	424	425	427	429	431	433	435	439	441	443	445	447	449	451	453	455	457	459	461									
	10-12	254-305	507	508	509	510	511	512	513	514	515	516	517	518	519	520	521	522	523	524	525	527	529	531	533	535	539	541	543	545	547	549	551	553	555	557	559	561									
	12-14	305-356			609	610	611	612	613	614	615	616	617	618	619	620	621	622	623	624	625	627	629	631	633	635	639	641	643	645	647	649	651	653	655	657	659	661									
	14-16	356-406				710	711	712	713	714	715	716	717	718	719	720	721	722	723	724	725	727	729	731	733	735	739	741	743	745	747	749	751	753	755	757	759	761									
	16-18	406-457					811	812	813	814	815	816	817	818	819	820	821	822	823	824	825	827	829	831	833	835	839	841	843	845	847	849	851	853	855	857	859	861									
	18-20	457-508						911	912	913	914	915	916	917	918	919	920	921	922	923	924	925	927	929	931	933	935	939	941	943	945	947	949	951	953												
FLOW RATE (gpm)*			0.05	0.06	0.07	0.09	0.10	0.12	0.15	0.17	0.19	0.24	0.26	0.29	0.34	0.37	0.40	0.44	0.48	0.51	0.56	0.66	0.78	0.90	1.00	1.13	1.45	1.62	1.79	1.95	2.10	2.24	2.40	2.59	2.90	3.11	3.30	3.62									
FLOW RATE (lpm)*			0.18	0.22	0.25	0.33	0.37	0.47	0.57	0.65	0.72	0.91	0.98	1.10	1.30	1.40	1.52	1.65	1.83	1.95	2.13	2.50	2.95	3.42	3.80	4.30	5.50	6.15	6.80	7.40	7.94	8.50	9.10	9.80	11.00	11.80	12.50	13.70									

FLOW RATE: WATER AT 1450 PSI, 100 BAR, 10 MPA | FAN WIDTH: AT 12 INCH, 305 MM FROM THE SURFACE



SWISS  
MADE

 POLYHOSE.US  732.512.9141  PHUS.SALES@POLYHOSE.COM

RAC® IS A REGISTERED TRADEMARK OF GRACO®. SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.